

UNDERBODY CYLINDER

TYPE : A DWR


SERIE : Ø 125

CYL. TYPE

A DWR 5.1460.125 - D130

For Tipping Weight See Advices Below

Technical Characteristics



Cylinder stages

Ø Stage	Ø045	Ø060	Ø075	Ø090	Ø105	Ø069	Ø088	Ø107	Ø126	Ø145	Ø165	Ø167	Ø187	Ø210	Ø236	Ø265
Thrust at 200 Bar [Tons]	3.20	5.60	8.80	12.70	17.50	---	---		---	---	---	---	---	---	---	---
Stages of cylinder	●	●	●	●	●											

Specifications

Stages number	05
Cylinder Stroke [mm]	1460
Cylinder weight only [kgs]	30.00
Working volume [Ltrs]	7.85
Max Working pressure [Bar]	200

Technical Information

<input type="checkbox"/> Oil	: See oil specification sheet
<input type="checkbox"/> Tipping weight	: Net weight + Payload
<input type="checkbox"/> Fitted centres [°]	: Closed centres plus 20 mm pull out

Advices

All our cylinders are manufactured to suit the particular application in the differing world markets/climate. Should you require details of the exact lifting capacity of the cylinder that has been selected for your application/veichle then please contact our technical department who will be only pleased to explain or advise.

Brackets and Accessories

Open brackets [2 Units per cylinder]	SSA#C	0.8 [kgs] x 1 =
Cradle	CU#AB	8.20 [kgs] x 1 =
Turning Adapter	RO#AN	0.18 [kgs] x 1 =

Recommendation

<input type="checkbox"/> This Binotto cylinder is designed as a lifting device only
<input type="checkbox"/> It must not be used as a structural member or be subject to side loads
<input type="checkbox"/> Pump flow in consultation with Binotto engineering department

BINOTTO SRL

BINOTTO IS CONSTANTLY ENGAGED IN IMPROVING ITS PRODUCTS AND THEREFORE RESERVES THE RIGHT TO MODIFY WITHOUT ANY NOTICE CHARACTERISTICS SHOWN

VIA DIVISIONE JULIA, 7/B - 36031 DUEVILLE [VI] ITALY • TEL. 0039.0444.593290 - FAX. 0039.0444.593357 • E-MAIL. INFO@BINOTTO.COM

Edit.: 01 • 2011

Rev.: 00 • 2010

Date: 23.01.2020

Pag.: A DWR 5.1460.125_06