

# 12 Series

## Low-Profile Signal Lighting



Part#	Description	EAN Code
12ARM	Stop / Tail / Indicator Lamp, Blister Pack	9335962034826
12FM	Rear Fog Lamp, Blister Pack	9335962036684
12WM	Reverse Lamp, Blister Pack	9335962036691

<b>Voltage</b>	9-32V
<b>Dimensions</b>	131 x 30 x 8mm
<b>IP rating</b>	IP67
<b>Warranty</b>	5 Years
<b>Cable</b>	250mm (stripped-end)
<b>Operating temperature</b>	-30°C to +50°C
<b>Current draw (13.8V / 28V)</b>	<b>Indicator:</b> 0.14A / 0.15A, <b>Stop:</b> 0.19A / 0.2A, <b>Tail:</b> 0.01A / 0.02A, <b>Fog:</b> 0.16A / 0.10A, <b>Reverse:</b> 0.21A / 0.21A

ECE approval	Function	Approval#
	Rear Indicator (R6)	2a-E9-01.22623
	Stop / Tail (R7)	R1-S1-E9-02.22623
	Fog (R38)	F1-E9-00.22188
	Reverse (R23)	AR-E9-00.22177

Wiring colour codes	YELLOW: Indicator [+]	BLUE: Fog [+]
	RED: Stop [+]	BROWN: Tail [+]
	BLACK: Reverse [+]	WHITE: Earth [-]

### Mounting instructions

**⚠ Installation to be undertaken by a competent professional**

#### 3M™ ADHESIVE EASY MOUNTING SYSTEM

Ensure mounting surface is flat, clean and dry prior to installation.

1. Peel the protective layer from one side of the mounting pad and fix to the rear of the lamp, aligning the breather holes.
2. Peel off the remaining protective layer, feed the wires through the hole in the vehicle surface and firmly press the lamp to fix into position.
3. Use screws for additional security if required.

