

950 LITRE U.N. APPROVED BUNDED DIESEL EU HIGHWAY BOWSER, c/w Hand Pump, Yellow

Technical Specifications

CHASSIS:

The bunded diesel EU highway bowser chassis is constructed from 100 x 50 RSC fully welded with front standing plate and an 'A' frame drawbar. Hot dip galvanised.



AXLE/SUSPENSION: Single Knott-Avonride 1500kg torsion beam axle fitted with 200 x 50 Auto reverse brakes.

WHEELS AND TYRES: 2 No 185 x 13 x 8 ply radial tyres. 4 stud 5 1/2" pcd rims.

COUPLING: Knott-Avonride 2000kg posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable & 40mm ring eye or 50mm ball.

COUPLING: Knott-Avonride 2000kg posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable & 40mm ring eye or 50mm ball.

ANCILLARY EQUIPMENT: Moulded mudguards, mud flaps, rear support stand, telescopic front jockey wheel, Side reflectors, front reflectors, full road lighting c/w 13 pin plug and 7 pin adapter. Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank. 4 lifting eyes, fork truck sockets for use when tank is not fitted in a chassis.

OUTER BUND TANK: Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank. 4 lifting eyes, fork truck sockets for use when tank is not fitted in a chassis.

INNER FUEL TANK: The bunded diesel EU highway bowser inner fuel tank is constructed from translucent heavy duty polyethylene with a capacity of 980 Litres. 2" filler with cap & chain. 1" manual vent valve. Pressure relief valve in the top of the tank. Ball valve in base of tank to pump.

PUMP: Comes standard with HAND PUMP, K1 semi rotary hand pump c/w in line 'Y' strainer, 15' of 1" fuel hose & trigger nozzle

Options available on request: Electric Pump, Petrol Pump, Non Resale Flowmeter.

FINISH: Tank- Primer and two top coats, single British Standard colour. Galvanised Chassis.

DELIVERY – TO BE QUOTED - Customer to offload forklift with extended forks will be required, to offload a curtain sided vehicle.

BUNDED DIESEL EU HIGHWAY BOWSER DIMENSIONS (APPROXIMATE):

- **WIDTH:** 1.550m (61")
- **HEIGHT:** 1.524m (60")
- **LENGTH:** 3.555m (140")
- **TOWING HEIGHT (Level):** 580mm
- **UNLADEN WEIGHT:** 476kg
- **LADEN WEIGHT:** 1300kg approx. – 1500kg max

Additional information

Extra's

- K33 Flowmeter (3Digit, Totaliser & Re-set)
- K24 Digital Flowmeter
- Pneumatic Pump Up Tank Contents Gauge
- 12v Battery In Plastic Box
- Solar Panel C/W 12v Battery In Plastic Box
- Additional 12v Fuel Pump
- Additional 110v Fuel Pump
- Additional 230v Fuel Pump
- Additional 1" Petrol Powered Fuel Pump
- Groz Water Filter
- External Generator Fittings
- Pressure Test Kit
- 2 x Number Plate Holders (Pair)
- Trickle Battery Charger (Connects To Car Via Grey Auxiliary Plug To Recharge Battery)
- 9kg Fire Extinguisher (On External Bracket)
- 90 Litre Spill Kit
- Spare wheel and holder Upgrade
- Auto Cut Off Nozzle (not available on hand pump units)

Welcome to the **UK's No1** tipper parts website. We supply everything your tipper needs and much more!



SEARCH



CLICK



PAY



DELIVER

www.thompsonseparts.co.uk

