

CS15 00

CYLINDERS WITH OUTER COVER

CS15 00 Cylinders Codes	N° of stages	Stroke (mm)	Mass (kg)	Swept Oil Volume (l)					A - Mounting Centre (mm) Tolerance - +40 / -0	B - Overall Height (mm)	C - Port Height (mm)	Port Type
					Tipping capacity		Bodylength (mm)					
					Min	Max	Min	Max				
CS15 00 4 4006 B19 A11	4	4006	199	51	37	57	5250	5750	345	1270	190	BSP
CS15 00 4 4206 B19 A11	4	4206	203	53	37	57	5400	5900	345	1320	190	BSP
CS15 00 4 4406 B19 A11	4	4406	211	56	37	56	5550	6050	345	1370	190	BSP
CS15 00 4 4606 B19 A11	4	4606	215	59	37	56	5700	6200	345	1420	190	BSP
CS15 00 4 4806 B19 A11	4	4806	222	61	37	55	5850	6350	345	1470	190	BSP
CS15 00 4 5006 B19 A11	4	5006	228	65	35	55	6000	7000	345	1520	190	BSP
CS15 00 4 5206 B19 A11	4	5206	234	67	35	53	6250	7250	345	1570	190	BSP
CS15 00 4 5406 B19 A11	4	5406	240	70	35	53	6500	7500	345	1620	190	BSP
CS15 00 4 5606 B19 A11	4	5606	245	72	37	53	6750	7750	345	1670	190	BSP
CS15 00 4 5806 B19 A11	4	5806	251	75	37	51	7000	8000	345	1720	190	BSP
CS15 00 4 6006 B19 A11	4	6006	257	77	36	50	7250	8250	345	1770	190	BSP

CS15 00 5 4277 B19 A11	5	4277	190	48	26	41	5500	6000	345	1125	190	BSP
CS15 00 5 4527 B19 A11	5	4527	196	52	26	40	5750	6250	345	1175	190	BSP
CS15 00 5 4777 B19 A11	5	4777	202	53	26	39	6000	6500	345	1225	190	BSP
CS15 00 5 5027 B19 A11	5	5027	209	56	26	38	6250	6750	345	1275	190	BSP
CS15 00 5 5277 B19 A11	5	5277	215	58	24	37	6500	7500	345	1325	190	BSP
CS15 00 5 5527 B19 A11	5	5527	220	62	24	36	6750	7750	345	1375	190	BSP
CS15 00 5 5777 B19 A11	5	5777	227	65	24	35	7000	8000	345	1425	190	BSP
CS15 00 5 6027 B19 A11	5	6027	233	67	24	35	7250	8250	345	1475	190	BSP
CS15 00 5 6277 B19 A11	5	6277	239	71	24	34	7500	8500	345	1525	190	BSP

SPECIALS

CS15 00 4 4206 N19 A11	4	4206	203	53	37	57	5400	5900	345	1320	190	BSP
CS15 00 4 4206 S19 A11	4	4206	203	53	37	57	5400	5900	345	1320	190	SAE
CS15 00 4 4606 N19 A11	4	4606	215	59	37	56	5700	6200	345	1420	190	BSP
CS15 00 4 5006 B25 A15	4	5006	212	65	35	55	6000	7000	1035	1520	250	BSP
CS15 00 4 5206 N19 A11	4	5206	234	67	35	53	6250	7250	345	1570	190	BSP
CS15 00 4 5606 B25 A14	4	5606	230	72	36	52	6750	7750	900	1670	250	BSP
CS15 00 4 5806 B19 A12	4	5806	247	75	36	51	7000	8000	550	1720	190	BSP
CS15 00 5 4277 S19 A11	5	4277	190	48	26	41	6000	6500	345	1125	190	SAE
CS15 00 5 4527 S19 A11	5	4527	196	52	26	40	5750	6250	345	1175	190	SAE
CS15 00 5 5027 B19 A13	5	5027	197	56	26	38	6250	7250	775	1271	190	BSP
CS15 00 5 5027 B25 A13	5	5027	199	56	26	38	6250	7250	775	1275	250	BSP
CS15 00 5 5277 S19 A11	5	5277	215	58	24	37	6500	7500	345	1325	190	SAE
CS15 00 5 6527 B19 F21	5	6527	246	76	25	36	7500	8500	345	1625	190	BSP
CS15 00 5 6277 T19 A11	5	6277	239	71	24	34	7500	8500	345	1525	190	BSP
CS15 00 5 6527 B19 F11	5	6527	251	76	25	36	7500	8500	345	1625	190	BSP
CS15 00 5 6777 B19 A11	5	6777	249	76	24	33	8000	9000	345	1625	190	BSP

