DATA SHEET

CRANE PADS



CP-4440Y | 400x400x40mm HI VIZ CRANEPAD



Colour: Yellow



Dimensions (w x d x h) mm: 400x400x40



Weight (kg): 6.30



Material: UHMW-PE (Ultra High Molecular Weight Polyethylene)



Load capacity (tonnes): 12.00



Handles: 1 x Rope



Resistance: Splintering, chemicals, corrosion, oil, water



PROPERTIES	UNIT	TEST METHOD	TEST RESULT
Density	g/cm3	ASTM D1505	0.93-0.955
Melting Point	°C	ASTM D-3418	133-135
Tensile Strength at Break	MPa	ISO 527:2012	14-16
Tensile Strength at Yield	MPa	ISO 527:2012	23-26
Elasticity Modulus	MPa	ISO 527:2012	1100-1210
Elongation at Break	%	ISO 527:2012	80-100
Charpy Impact Strength-Notched	KJ/m²	ISO179-1:2011	33-37
Hardness	Shore D	ISO868:2003	67-69
Wear Resistance Sand-Slurry-Test	%	ISO15527	372
Average Coefficient of Linear Thermal Expansion	m/(m/k)	-	2x10-4
Service Temperature	°C	-	-100 to +80

Note: $1g/cm^3 = 1,000 \text{ kg/} \text{ m}^3$; $1Mpa = 1N/mm^2$; 1kV/mm = 1MV/m