

The KM 634 is a robust and powerful tool for logs – especially for heavy duty operation. Well suited for handling single trunks.

- ▷ **Low height** with one horizontal hydraulic cylinder – especially when closed due to the interlocking arms.
- ▷ **Long service life** is ensured by the sturdy construction, high quality components and generously dimensioned bearing system. All bearing bolts are case hardened and housed in steel bearing bushes.
- ▷ **Optimised design** allows extremely small grapple diameter – ideal for handling thin timber securely. The arms open almost vertically. That enables an easy penetration into the timber stack.
- ▷ **Synchronisation** of arms due to sturdy compensation rods.
- ▷ **Protection of the hoses** for the hydraulic connections by a hose guard on the KINSHOFER rotator.
- ▷ **Precise positioning** of the loads is no problem in combination with the KINSHOFER rotator – continuous rotation, precise start and stop ability.
- ▷ **Safety** is assured in the event of an unexpected pressure drop due to the integrated non-return valve.
- ▷ **Reinforced version KM 634S** with more sturdy construction and equipped with a stronger rotator.



KM 634-0.35

**Packages logging grapple KM 634 c**

Type	Capacity (m <sup>2</sup> )	Width E (mm)	min. Log-Ø D2 (mm)	max. Log-Ø D1 (mm)	Opening A max. (mm)	Weight (kg)	Load capacity (kg)
KM 634-0.25 c	0.25	420	90	460	1,470	215	4,000
KM 634-0.35 c	0.35	500	135	590	1,950	300	5,000

**Package consists of:** logging grapple, rotator with hose guard (for KM 634-0.25: KM 06 F173-35, for KM 634-0.35: KM 10 F173-35), short connecting hoses KM 203 01, upper suspension KM 501 suiting rotator size, non-return valve

**Logging grapple KM 634**

Type	Capacity (m <sup>2</sup> )	Width E (mm)	min. Log-Ø D2 (mm)	max. Log-Ø D1 (mm)	Opening A max. (mm)	Weight (kg)	Load capacity (kg)
KM 634-0.25	0.25	420	90	460	1,470	170	4,000
KM 634-0.35	0.35	500	135	590	1,950	225	5,000
KM 634-0.50	0.50	500	170	650	1,985	250	5,000

**Reinforced logging grapple KM 634S**

Type	Capacity (m <sup>2</sup> )	Width E (mm)	min. Log-Ø D2 (mm)	max. Log-Ø D1 (mm)	Opening A max. (mm)	Weight (kg)	Load capacity (kg)
KM 634S-0.40	0.40	510	135	590	1,950	270	6,000
KM 634S-0.50	0.50	510	170	650	1,985	275	7,000
KM 634S-0.70	0.70	590	110	870	2,570	530	8,000

**Accessories**

Type	Description
KM 06 F173-35	recommended KINSHOFER rotator for KM 634-0.25
KM 10 F173-35/1	recommended KINSHOFER rotator for KM 634-0.35
KM 10 F173-45	recommended KINSHOFER rotator for KM 634S

**Requirements of truck crane**

**Operating pressure at oil flow:**  
max. 24 MPa (240 bar) at 25 - max. 75 l/min **Mind the pressure!**

**Technical drawings**

